



SEL-LPS Linear Power Supply



Major Features and Benefits

The SEL-LPS is a general-purpose dc supply for testing protective relays and for general application.

- ▶ **Flexible.** Multiple outputs of one power supply serve many devices. Connect protective relays, communications processors, and other devices to two 24-Vdc and two 125-Vdc outputs (50 VA maximum). You can connect the two 24-Vdc outputs in series for 48 Vdc or connect the two 125-Vdc outputs in series for 250 Vdc.
- ▶ **Rugged.** Linear design provides “stiff” low-impedance outputs to start and serve high-surge loads.
- ▶ **Regulated Outputs.** Connect station or plant support equipment (transducers, sensors, and more) to the general-purpose +5-Vdc, +15-Vdc, and -15-Vdc regulated outputs.
- ▶ **Popular Input Voltages.** Use anywhere that commercial ac power is available; 120 Vac or 230 Vac, 50 Hz or 60 Hz rated systems.
- ▶ **Convenient and Safe.** Quickly wire output connections and easily view operating status on the front panel. Safely power relays in laboratories, classrooms, and offices.

Specifications

General

Power Supply

Input:	90–132 Vac, 50/60 Hz, or 200–240 Vac, 50/60 Hz 75 VA maximum
Outputs:	See <i>Table 1</i>
Fuse:	1.6 A, 250 V slow blow (Littelfuse 218 01.6, 5 x 20 mm fuse, or equivalent)

Operating Temperature

0° to 50°C (32° to 122°F)

Physical Specifications

Dimensions

114.3 mm H x 285.8 mm W x 241.3 mm D
(4.5 in. H x 11.25 in. W x 9.5 in. D)

Unit Weight

4.1 kg (9 lbs)

Table 1 Output Parameters

Number of Outputs	Rating	Output Current	Output Voltage	Comments
2	+125 Vdc	0.2 A ^a	125 Vdc nominal (unregulated)	Isolated
2	+24 Vdc	1.0 A ^a	24 Vdc nominal (unregulated)	Isolated
1	+5 Vdc	500 mA	4.75 to 5.25 Vdc	Referenced to ground
1	+15 Vdc	250 mA	14.25 to 15.75 Vdc	Referenced to ground
1	–15 Vdc	250 mA	–15.75 to –14.25 Vdc	Referenced to ground

^a 50 VA maximum

© 2006 by Schweitzer Engineering Laboratories, Inc. All rights reserved.

All brand or product names appearing in this document are the trademark or registered trademark of their respective holders. No SEL trademarks may be used without written permission. SEL products appearing in this document may be covered by US and Foreign patents.

Schweitzer Engineering Laboratories, Inc. reserves all rights and benefits afforded under federal and international copyright and patent laws in its products, including without limitation software, firmware, and documentation.

The information in this document is provided for informational use only and is subject to change without notice. Schweitzer Engineering Laboratories, Inc. has approved only the English language document.

This product is covered by the standard SEL 10-year warranty. For warranty details, visit www.selinc.com or contact your customer service representative.

SCHWEITZER ENGINEERING LABORATORIES

2350 NE Hopkins Court • Pullman, WA 99163-5603 USA

Phone: (509) 332-1890 • Fax: (509) 332-7990

Internet: www.selinc.com • E-mail: info@selinc.com

