

SEL-501-0, -1, -2 Connectorized®

Dual Overcurrent Relay, Standard With 5 Outputs, 2 Inputs, Plug-In Connectors, and High Current Interrupting Output Contacts

Part Number:

0 5 0 1 W

Firmware

Standard With all Application Setting Options*		0									
Standard plus Additional Square D Sy/MAX® Protocol (5 A, 60 Hz, ABC phase rotation only)*		1		5	6		X	B			
OC1 Application Setting Option Only		2									

Power Supply

24 Vdc				1							
48/125 Vdc or 125 Vac				3							
125/250 Vdc or Vac				6							

Conformal Coat

None					X						
Conformally Coated Circuit Boards*					2						

Secondary Input Current; Frequency; Phase Rotation

1 A Phase; 50 Hz; ABC						1	5			B	
1 A Phase; 60 Hz; ABC						1	6			B	
1 A Phase; 60 Hz; ACB						1	6			C	
5 A Phase; 50 Hz; ABC						5	5			B	
5 A Phase; 60 Hz; ABC						5	6			B	
5 A Phase; 60 Hz; ACB						5	6			C	

Communications Port⁽¹⁾

EIA-232								1			
EIA-485*								2			

Packaging

Horizontal Rack Mount										X	
Part of Two-Relay Rack Mount Package										P	
Single Relay Assembled With Rack Mount Bracket 9100 (bracket on right side in front view)										B	
Single Relay With Rack Mount Bracket 9102 w/Cutout for Test Switch (bracket on right side in front view)										C	
Horizontal Panel Mount										3	
Horizontal Projection Panel Mount*										5	

Communications Protocol

Standard										X	
Standard plus Modbus® (not available with Sy/MAX protocol, 05011)										2	

Control Input Voltage

24 Vdc											1
48 Vdc (level sensitive inputs)											2

110 Vdc (level sensitive inputs)															3
125 Vdc (level sensitive inputs)															4
250 Vdc (level sensitive inputs)															6

Accessories

Literature			
	SEL-501-0, -1 Printed Instruction Manual ⁽²⁾	P	M 5 0 1 - 0 1
	SEL-501-2 Printed Instruction Manual ⁽²⁾	P	M 5 0 1 - 0 2
Wiring Harness			
	Wiring Harness for Connectorized SEL-501 ^{(3)*}	Please see Online MOT or contact SEL REP or CSR for ordering information.	

* Additional Cost

⁽¹⁾ Warning - EIA-485 is for special applications only. SEL strongly recommends ordering an EIA-232 port. If an EIA-485 port is ordered, SEL strongly recommends cable C671A to allow relay programming and event retrieval. All SEL-501 relays ordered with an EIA-485 port are shipped with a C675 Terminal Adapter to adapt from the on board DB-9 connector to an 8-pin screw terminal.

⁽²⁾ The SEL-501-0, -1, -2 Connectorized comes standard with a CD manual. One complimentary printed instruction manual is available upon request with each product purchased.

⁽³⁾ Order a Connectorized[®] Wiring Harness for SEL-501 (harness shipped separately).

Making Electric Power Safer, More Reliable, and More Economical[®]

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990