

Wiring Harness for Connectorized SEL-487E

Wiring Harness for Connectorized® SEL-487E Relays, Features CT Shorting Connector⁽¹⁾. Wiring Harness Provides Connectors and Wiring for 18 AC Current Inputs and 6 AC Voltage Inputs.

Part Number:

W	A	0	4	8	7	E					A
---	---	---	---	---	---	---	--	--	--	--	---

Wire Size for Current Inputs

#10*										A			
#12										B			
#14										C			
#16										D			

Wire Size for Voltage Inputs and Power

#14										C			
#16										D			
#18										E			
No Voltage Cable Harness (LEA Voltage Inputs) ⁽²⁾										F			

Wire Length

4 Feet												1	
8 Feet												2	
12 Feet*												3	
16 Feet*												4	
20 Feet*												5	

Wire Type

XLP (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90° C; Voltage Rating: 600 Volts)													A
--	--	--	--	--	--	--	--	--	--	--	--	--	---

* Additional Cost

⁽¹⁾ To Order Test Harness, Specify Part Number WA0487E-0002
 - Wire Length: 6 inches
 - Terminated with Banana Jacks
 - No Wire Options

⁽²⁾ SEL-487E-3 or SEL-487E-4 Relays with Low Energy Analog (LEA) voltage inputs do not include a voltage cable harness.

Making Electric Power Safer, More Reliable, and More Economical®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA
 Phone: +1.509.332.1890 - Fax: +1.509.332.7990