

SEL-C659 EIA-232 Serial Cable with IRIG-B

Cable for connecting an SEL-3390S8 Serial Card of the SEL-3355 Computer to a DTE device with a 9-pin female connector.⁽¹⁾

Part Number:

C 6 5 9 -


Length⁽²⁾

Specify in feet with leading zeros (Example: 5 Feet = 005) Max length 100 Feet

*Additional Cost

⁽¹⁾ To verify your cable application, use the Cable Selector at <https://www.selinc.com/CableSelector>

⁽²⁾ The performance of EIA-232 cable lengths greater than 50 feet cannot be guaranteed. As cable lengths increase, so does the risk of interference and equipment damage due to ground potential rise and induced voltages.



SEL-3390S8			EIA-232 (DTE)	
+5 VDC/DCD	2	GREEN/WHITE	1	+5 VDC/DCD
GND	4	BLUE	5	GND
RXD	5	BLUE/WHITE	3	TXD
TXD	6	GREEN	2	RXD
CTS	7	BROWN/WHITE	7	RTS
RTS	8	BROWN	8	CTS
SHELL		SHIELD		NO CONNECTION
			IRIG-B Input	
GND	1	ORANGE/WHITE		SHIELD
+IRIG-B	3	ORANGE		CENTER

Comments: SEL-3390S8 Serial Card pin 2 factory default configuration is DCD input.
+5Vdc output can be enabled via software settings.

Making Electric Power Safer, More Reliable, and More Economical®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990