

## SEL- C607 Serial Cable

Cable for connecting a device with an EIA-422/485 terminal block connection to a device with an RJ-45 connector.<sup>(1)</sup>

Part Number:

**C 6 0 7 -**

### Length<sup>(2)</sup>

Specify in feet with leading zeros (Example: 5 Feet = 005) Max length 330 Feet

<sup>(1)</sup> To verify your cable application, use the Cable Selector at <https://www.selinc.com/CableSelector/>.

<sup>(2)</sup> As cable lengths increase, so does the risk of interference and equipment damage due to ground potential rise and induced voltages.



**CABLE:** 4 pair (Stranded) Twisted Shielded CAT 5E Cable

1	ORANGE/WHITE
2	ORANGE
3	GREEN/WHITE
4	BLUE
5	BLUE/WHITE
6	GREEN
7	BROWN/WHITE
8	BROWN
SHELL	SHIELD

**Comments:** For the SEL-ICON Async Data Submodule and SEL-3355 (3390S8) serial card, please reference the instruction manuals for cable pinout.

*Making Electric Power Safer, More Reliable, and More Economical<sup>®</sup>*

**SEL** SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA  
 Phone: +1.509.332.1890 - Fax: +1.509.332.7990