Wiring Harness for Connectorized SEL-451

Features CT Shorting Connector[1]

Part Number:	W	A	0	4	5	1	0				A

Wire Size for Current Inputs

#10*								A			
#12[2]								B			
#14								C			
#16								D			

Wire Size for Voltage Inputs and Power

#14[2]									C		
#16									D		
#18									E		
No Voltage Cable Harness (LEA Voltage Inputs)[3][4]									F		

Wire Length

4 Feet										1	
8 Feet[2]										2	
12 Feet*										3	
16 Feet*										4	
20 Feet*										5	

Wire Type

XLP[2] (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90°C; Voltage Rating: 600 Volts)											A

* Additional Cost

(1) To order test harness, specify part number WA0451-0001.
Wire Length: 6 inches
Terminated with banana jacks
No wire options

(2) Standard options. Specify part number WA04510BC2A.

(3) SEL-451-5 relays with Low Energy Analog (LEA) voltage inputs do not include a voltage cable harness.

(4) Standard option (LEA). Specify part number WA04510BF2A

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.
2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990

Copyright © SEL 2019
All rights reserved.

WI-16126
20190711