

**SEL-735 Power Quality and Revenue Meter With Color Touchscreen**

Part Number:

0	7	3	5	L	2	0					X			X	X			2	0		X
---	---	---	---	---	---	---	--	--	--	--	---	--	--	---	---	--	--	---	---	--	---

Enclosure Type

None											X										
Easily Extractable Meter (EXM)*											E										
NEMA 4 With FT-1 Test Switch ^{(1)*}											B									2	
Portable Case ^{(1)(2)*}										C			4	4	E	X		X	X		2

Metering Form

Form 5 (Three-Wire Delta; 2 PTs, 2 CTs)												5									
Form 9 (Four-Wire Wye; 3 PTs, 3 CTs)													9								
Form 36 (Four-Wire Wye; 2 PTs, 3 CTs)														6							

Slot A Power Supply Voltage

24-48 Vdc														2							
125-250 Vdc (120-240 Vac)															4						

Slot A Control Input Voltage

o Includes 3 Contact Outputs, 2 Inputs

24 Vdc/Vac														2	1						
48 Vdc/Vac															2	2					
125 Vdc/Vac															4	4					
250 Vdc/Vac																4	6				

Slot B Ethernet (Port 1) | Rear Serial (Port 3)

o Includes EIA-232 Standard

Single 10/100BASE-T EIA-232																	C				
Single 10/100BASE-T EIA-485																	E				
Single 100BASE-FX Multimode EIA-485*																	G				
Single 100BASE-LX10 Single-Mode EIA-485*																	J				

Slot C Communications

Field Upgrade Available

Empty																	X				
Serial Communications o EIA-232 and EIA-485 Ports*																	F				
Telephone Modem*																	G				

Slot D I/O

Field Upgrade Available

Empty																	X	X			
4 DI / 4 DO Solid-State*																	A				
4 DI / 4 DO Electromechanical*																	B				
4 AO (± 1 mA) / 4 DO Solid-State*																	C	X			
4 AO (± 20 mA) / 4 DO Solid-State*																	D	X			

