SEL-WA0300G_W

Wiring Harness for SEL-300G_W Connectorized® Relays, Features New Shorting Connector[1]

Part Number: **W A 0 3 0 0 G _ W _ _ _ A**

Relay Configuration

Standard	0
Standard plus Differential	1
Standard plus Synch-Check	2
Standard plus Synch-Check and Differential	3

Wire Size for Current Inputs

#10*	A
#12[2]	B
#14	C
#16	D

Wire Size for Voltage Inputs and Power

#14[2]	C
#16	D
#18	E

Wire Length

4 Feet	1
8 Feet[2]	2
12 Feet*	3
16 Feet*	4
20 Feet*	5

Wire Type

XLP[2] (Wire Insulation: Crosslinked Polyethylene (XLP); Temp. Range: -40° to 90°C; Voltage Rating: 600 Volts)	A

[1] To order test harness, specify part number WA0300G3W.
Wire Length: 6 inches
Terminated with banana jacks
No wire options

[2] Standard options. Specify part number WA0300G0WBC2A, WA0300G1WBC2A, WA0300G2WBC2A, or WA0300G3WBC2A.

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.
2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990

Copyright © SEL 2000-2016
All rights reserved.

WI-1743
20160613